

Claims

1. An apparatus for the detection of movements and/or positions of an object, in which a voltage pulse
5 is in each case produced as a function of the movements and/or positions of the object in at least one coil, by means of at least two magnets which carry out a relative movement with respect to the coil and act on it with their fields, with
10 the north-south axes of the respective two adjacent and opposite-polarity magnets which form a magnet pair being oriented, in the same way as the longitudinal axis of the coil, essentially at right angles to the movement direction of the
15 object, **characterized in that** the magnets (6, 7) are arranged one behind the other in the direction of movement of the object (1, 24, 32), and the coil (4) at least partially surrounds a spring (5) which is composed of magnetically permeable
20 material and whose end facing the magnets (6, 7) carries out a reciprocating movement as a result of the reluctance effect under the influence of the fields of the magnets (6, 7) of the magnet pair, which reciprocating movement causes a
25 polarity change, which produces the respective voltage pulse, in the magnetic field in the coil (4) .
2. The apparatus as claimed in the precharacterizing
30 clause of claim 1, **characterized in that** the magnets (44, 45) are arranged alongside one another when considered in the direction of their relative movement with respect to the coil (52) and the coil (52) at least partially surrounds a
35 spring (46) which is composed of magnetically permeable material and whose end facing the magnets (44, 45) carries out a reciprocating

- movement on the basis of the reluctance effect under the influence of the fields of the magnets (44, 45) of the magnet pair, which reciprocating movement causes a polarity change, which produces the respective voltage pulse, in the magnetic field in the coil (52), with both the pole surfaces of the magnets (44, 45) and that end surface of the leaf spring (46) which faces the pole surfaces of the magnets (44, 45) being essentially in the form of rectangles, whose longitudinal axes include an angle (α) of less than 60° with the tangent to the movement path (48) of the magnets (44, 45).
- 5
- 10
- 15 3. The apparatus as claimed in claim 1 or 2, **characterized in that** the spring (5; 46) is in the form of a leaf spring which is clamped in at one end.
- 20 4. The apparatus as claimed in one of claims 1 to 3, **characterized in that** the mutually directly adjoining magnets (6, 7; 44, 45) are firmly connected to a moving mount (1; 26; 31; 51).
- 25 5. The apparatus as claimed in one of claims 1 to 4, **characterized in that** the moving object (1) is formed by the shaft of a tachometer.
- 30 6. The apparatus as claimed in claim 5, **characterized in that** the shaft (1) of the tachometer is provided with a concentric collar (25) which at least partially surrounds it and on whose inner wall (26) facing the shaft (1) the magnets (6, 7) are mounted.
- 35 7. The apparatus as claimed in claim 6, **characterized in that** at least one coil (4), which is provided

with a spring (5), is arranged in the space between the inner wall (26) of the collar (25) and the shaft (1).

- 5 8. The apparatus as claimed in one of claims 1, 3 or
4, **characterized in that** at least one coil (4),
which is provided with a spring (5), is arranged
in a sensor head (34) which is connected to an
object (32) which moves along a scale (29), with
10 the scale to be scanned by the sensor head (34)
comprising at least two sections (29a, 29b) at
whose abutment or joining point a magnet pair (6,
7), which interacts with the coil (4), is in each
case arranged.
- 15 9. The apparatus as claimed in claim 8, **characterized
in that** the sensor head (34) is equipped with two
coils (4, 4) which each surround one spring (5).
- 20 10. The apparatus as claimed in one of claims 8 or 9,
characterized in that the scale (29) is in the
form of a linear scale which is provided with an
absolute coding (30) which can be read by scanning
electronics (35) of the sensor head (34).
- 25 11. The apparatus as claimed in one of claims 8 to 10,
characterized in that the moving object is formed
by the carriage (32) of a machine tool.
- 30 12. The apparatus as claimed in one of claims 1 to 11,
characterized in that the apparatus carries out
the function of a voltage generator.
- 35 13. The apparatus as claimed in one of claims 1 to 12,
characterized in that the voltage pulses which are
produced can be used as signals which can be
supplied to an electronic counting circuit.

14. The apparatus as claimed in claim 2, **characterized in that** the longitudinal axes of the essentially rectangular pole surfaces of the magnets (44, 45) include an angle (α) of 20 to 30° with the tangent to the movement path of the magnets (44, 45).
15. The apparatus as claimed in claim 2 or 14, **characterized in that** both the width and the length of the pole surface of the magnets (44, 45) is greater than the width and the length of the end surface of the leaf spring (46).
16. The apparatus as claimed in claim 15, **characterized in that** the length and the width of the pole surfaces of the magnets (44, 45) are in each case a multiple of the length and width of the end surface of the leaf spring (46).
17. The apparatus as claimed in one of claims 2 or 14 to 16, **characterized in that** the leaf spring (46) is clamped in at its end facing away from those pole surfaces of the magnets (44, 45) which pass it, between two holding plates (54, 55) which are provided with damping inserts.
18. The apparatus as claimed in one of claims 1 to 17, **characterized in that** the free end of the spring (5; 46) projects slightly beyond the end of the coil (4; 52) which surrounds it.
19. The apparatus as claimed in one of claims 1 to 7 or 14 to 18, **characterized in that** the mount (51) is formed by a disk which is connected to the shaft (50) of a tachometer.
20. The apparatus as claimed in one of claims 1 to 19,

characterized in that the magnets (6, 7; 44, 45), which are arranged in pairs, are associated with a plurality of coils (4, 4'; 52, 52') which are each equipped with one spring (5; 46).

5

21. The apparatus as claimed in claim 20,
characterized in that the magnets (6, 7; 44, 45), which revolve with the shaft (1; 50), have two associated coils (4, 4'; 52, 52'), which are each
10 equipped with one spring (5; 46), and the distance between the coils (4, 4'; 52, 52') is greater than the extent of the magnets (6, 7; 44, 45) in the direction of their movement.

15 22. The apparatus as claimed in claim 20 or 21,
characterized in that two coils (4, 4'; 52, 52') are in each case electrically connected back-to-back in series with one another.

20 23. The apparatus as claimed in one of claims 1 to 7 or 14 to 22, **characterized in that** the apparatus is provided with sensors (68-70) which can be acted on by means of at least one actuator (67) and are used for the detection of the movements
25 and/or positions of an object, while the magnets (44, 45; 44', 45; 44", 45") are used only to supply power to a microprocessor circuit (E).

30 24. The apparatus as claimed in claim 23,
characterized in that the actuator (67) is in the form of a magnet, and the sensors are in the form of MR or Hall sensors (68-70).